



DOA

Hydraulic Tools



KV25
BREAKER



MHU9
POWER PACKS

MHU9

POWER PACKS

20 L/min @ 140 Bar Engine 9 Hp - Recoil starter

GASOLINE

- *Stainless steel frame*
- *All parts suspended on anti-vibration shock mounts*
- *Quick couplers installed on impact free swivel fittings*
- *High efficiency oil cooling system with centrifugal fan*
- *Central lifting hook*
- *Power on demand for better fuel economy and reduced environmental impact*



The **MHU9** is our go to power pack for the rental, contractor, utility and USAR sectors offering a light portable solution capable of powering the most demanding hydraulic tools. It features power on demand and a robust Stainless-Steel frame designed for the toughest of environments.

| TECHNICAL CHARACTERISTICS | MHU9 |
|---------------------------|---------------------------|
| Weight (kg) | 60 |
| Dimension LxWxH (mm) | 700x500x570 |
| Flow L/min | 20@140 Bar |
| Pressure Bar | 140/210 |
| Engine | 9hp - gasoline |
| Engine model | Briggs & Stratton - Honda |
| Starter | recoil |
| Acceleration | power on demand |
| Hoses Length std | 7 mt |



KV25

BREAKER

The KV25 conforms to all CE regulations for noise, vibration and safety trigger

- *Anti vibration handle according to the newest CE regulations allows operators comfort and safety*
- *Available in 20 LPM or 30 LPM versions, depending on application.*
- *Only one dynamic seal and few moving parts to assure maximum reliability and a unbeatable operative longevity*
- *High tolerance to back pressure allows peak performance even with extended hose lengths.*
- *No vulnerable plastic parts*
- *Slim tool profile without side rods or sharp angles assures maximum ergonomics*
- *Available special percussion heads configured to dig in electric earthing pickets or small poles*



The **KV25** hydraulic breaker comes with "T type" anti-vibration handles suspended on springs and ergonomically designed for the comfort of the operator. It is well suited for general demolition works, the breaking of concrete and asphalt cutting. Our KV25 gives the best compromise between high power and maneuverability, it can be powered by a power pack or the hydraulic circuit of a mini excavator, SSL, truck/van, or other machines with a sufficient hydraulic circuit. The hydraulic system assures quietness and productivity, eliminating the typical problems associated with the transport and performance of bulky air compressors and pneumatic breakers.

| TECHNICAL CHARACTERISTICS | KV 25 |
|---------------------------|-----------------------------------|
| Weight (kg) | 25 |
| Dimension LxWxH (mm) | 752x429x140 |
| Tool bit size mm | Hex. 1-1/4" x 6-1/4" (32 x 160mm) |
| Flow L/min | 20-30 |
| Ideal flow L/min | 20 |
| Pressure Bar | 90-110 |
| Blow frequency/min | 1050 (20l/min) |
| Impact energy | 113 J |
| Vibration m/s 2 | 7.79 |
| Handle type | "T" anti vibration |





DOA
Hydraulic Tools

22066 Mariano Comense (CO) - ITALY
Via Sant'Agostino 158
Tel. (+39) 031 792 040
www.doa.it - info@doa.it